

SECURATRAK PRODUCT SHEET

Mandown / Duress Solutions

PRODUCT FEATURES

The Mandown and Duress solutions that Securatrak provide are of the highest standards, and have been extensively tested for successful integration into our LIVE GSM & SATELLITE GPS in-vehicle tracking solutions.

Our duress products operate on the 433 MHz band, and when installed correctly, and with "optimum line of site coverage", will provide up to 300m range from the vehicle.

You can register unlimited numbers of the handheld personal duress units to any single in-vehicle receiver.

When triggered by the user in an emergency situation, the location and time, is sent back to our Geotab Checkmate Software creating an alert for you to respond to.

PRODUCT MODELS

Basis Duress Version Handset: enables the user to activate an alarm event by pushing the "Alarm" button on the face of the unit or by using the pull cord activation method.

Advanced Duress Version Handset: has the same functionality as the Basic unit, with the added ability of activating an alert via the following;

- No-movement sensor—activates when a unit remains motionless for a preset period of time.
- Man-down sensor—activates when a unit is laid down horizontally for a preset period of time.

Therefore in the event that the operator is incapacitated and unable to manually respond, the unit will automatically send an alert.



 **Securatrak**
FLEET MANAGEMENT SOLUTIONS

Securatrak Pty Ltd

HEAD OFFICE : 79 Belair Road, Kingswood, SA 5062

ADELAIDE | PERTH | BRISBANE | SYDNEY | MELBOURNE | AUCKLAND

Technical Data and Specifications

Mandown / Duress Solutions



Basis Duress: Handheld push button only.
Advanced Duress: Plus Mandown & No Movement
Range: Up to 300 meters line of sight from receiver
Wearing: Belt clip or as an option a carry case with a belt clip or a belt loop
Battery: Rechargeable – Li-Ion
Standby Time: Approx 7 days between recharge, based upon 1 trigger per day.
Weight: 93g incl. batteries
Protection: IP40, IEC EN600529
Dimensions: (l x w x d): 85 x 57 x 33 mm
Alarms: Test, Push button (1 press and 2 press) plus Pull-cord alarm.
No-movement and Man-down alarm as an option.



Description: Small UHF alarm receiver
Alarm indication: Polarized and voltage-free make/brake outputs
 >Output 1: Test alarm
 >Output 2: Transmitter alarm
 > Output 3: Function alarm
Transmitter capacity: Unlimited
Dimensions: (l x w x d): 80 x 80 x 48 mm
Weight: 125 g
Supply voltage: 7 - 24 VAC / VDC



PRODUCT	CODE	RRP (Inc. GST)
Duress Push button & Pull cord (Basic)	AMIE-AAABA/A	\$725.00
Duress Push button & Pull Cord & Mandown & No Movement (Advanced)	AMIE-AAABB/A	\$859.00
Duress unit charger	660109	\$65.00
Duress Mini Receiver includes antenna	MD576/B	\$699.00

Securatrak Pty Ltd

PHONE: 1300 653 395

HEAD OFFICE : 79 Belair Road, Kingswood, SA 5062

ADELAIDE | PERTH | BRISBANE | SYDNEY | MELBOURNE | AUCKLAND